



AZLED/3

Z LED High Bay UFO 198W 4000K



Features

Robust LED low/high bay for industrial, commercial and retail applications

Pre-wired with 3m of H07RN-F cable for ease and speed of installation

Alternative installation options by means of drop rods, jack chain / catenary wire

198W comparable to 400W HQI

Die-cast powder coated construction and heatsink for optimum thermals and performance

TP(a) as standard

LED lifespan L70 50,000 hours

1-10V dimmable as standard

General Information

Lamp Type	LED
Colour / Finish	Black
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Suspended
LED Life	L70 50,000hrs
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	400
Depth (mm)	188
Accessories	AZLED/REF, AZLED/FB1

Technical Information

Wattage	198W
Lumens Delivered	23965lm
Lm/W	121lm
CRI	Ra 80
CCT	4000K
Input	200-240V
Hertz	50/60Hz
Operating Temp	-40°C to 40°C

Technical Data - ETIM - High bay luminaire (EC001716)

Mounting method	Pendant
With light source	Yes
Suitable for number of lamps	1
Material housing	Aluminium
Nominal voltage	200-240 V
Control gear included	Yes
Dimming 1-10 V	Yes
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class	I
Max. system power	198 W
Rated luminous flux acc. IEC 62722-2-1	23965 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Height/depth	188 mm
Outer diameter	400 mm
Suitable for emergency lighting	No

Datasheet generated from <https://onetimepim.com> last updated Monday, November 4, 2019 1:29:08 PM

