


## Pace PLUS Backlit 600x600 Panel



- Industry leading super high efficiency (up to 180lm/W) backlit LED panel suitable for education, commercial and ancillary area applications
- Slimline design allows for installation into shallow ceiling voids
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Power selectable; offering a choice of 3 outputs, in one luminaire
- Self-Test Panel Pod and Sensor Pod compatible
- Dimmable and OCTO options available
- TPa as standard
- Self-Test Panel Pod and Sensor Pod compatible (see p522 for more information)



OCTO  
Option  
Available

Powered by  
CASAMBI



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220-240V	50-60Hz	-10°C to 40°C	L80 98,000	Ra 80	<5	80°	2	IP44

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
APACP/60/CW	600 x 600 Cool White	11.5W		2050lm			
		13.5W	4000K	2400lm	180lm	18	
		17W		3000lm			

\* UGR Value based on (4H - 8H)

AIRMLD/POD/3NM/ST	Emergency Pod	5W
AIRMLD/POD/MWS	Sensor Pod	1W

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (ACCESSORIES)	DESCRIPTION	TRADE
/DM3	DALI Emergency		APACLED/SK	Pace Suspension Kit	
/OCTO	OCTO Smart Control		AERMLD/60/SMF	600x600 Surface Mounting Frame	
/DD	Digital Dimming (DD1/DD3/DD4)		APRK/60	600x600 Plasterboard Recessed Kit	