

## **Technical Specification**



Product Code: CMA024	Description: 20A Double Pole Sink/Ba	ath Plate Switch With Neon
BATH OF SINK O	FF T	SIPPLY BATHL SINKL SIPPLY BATHL SINKL COLORS BEREOGOS COLORS COLORS COLORS
General Informat	tion	
Plate Dimensions (	mm) 86 (W) × 86 (H) × 9.5 (D)	
Plate Fixing Centres - Horizontal (		
	Style Rounded Profile	
	nish Polar White	
Mate		Rear Housing: Urea
	Neon Lens: Polycarbonate	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivate	ed Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Anti Microbial Cert	ified Yes	
Rated Voltage (V~)	(Ue) 250	Frequency (Hz) 50
Resistive Load Rating		
Termination		
Terminal Size (		minal Torque Value (Nm) 1.8
Terminal Capacity - Solid (n		
Double Pole Sw		
Twin Earth Termi		
Neon India		Indicator Colour Orange
Product Mar		
Minimum Back Box Depth (	-	
Ingress Protect		
Operational Temperature		
Warranty (Ye		
	EN 60669-1	
	r cleaning / poliching of products, use only a set	t dry clean clath
	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit	
	diagram with the relevant product.	
	Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.	
	All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent	
properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral		
properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-		
enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of		
	bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.	

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (14/09/22) Errors & Omissions excluded. Specification is subject to change without notice.