

## **Technical Specification**



Product Code: CMA157 Description: Isolated Satellite & Isolated Coaxial Outlet





Earth Plate: Mild Steel

## **General Information**

Plate Dimensions (mm) 86 (W)  $\times$  86 (H)  $\times$  9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Rounded Profile
Finish Polar White

Materials Front Plate: Urea

Terminals: Brass

Anti Microbial Certified Yes
Termination Type Screw

**Isolated** Yes

Non-Isolated No Shielded No Minimum Back Box Depth (mm) 16

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Warranty - Electronics (Years) 1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

