

Technical Specification



Product Code: CMA623

General Information

Description: 20A Double Pole Plate Switch With Neon



Plate Dimensions (m Plate Fixing Centres - Horizontal (m St Fin Materi	m) 60.3 yle Rounded Profile sh Polar White	. ,	Rear Housing : Urea	
	Neon Lens: Polycarb		Terminals: Brass	
		el & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: For	med Pressed Brass	Earth Strap: Mild Ste	el
Anti Microbial Certif				
Rated Voltage (V~) (I	,		Frequency (Hz)	50
Resistive Load Rating	. ,			
Termination Ty	•	Taurainal		1.0
Terminal Size (m Terminal Capacity - Solid (mr		Terminal	Torque Value (Nm)	1.8
Double Pole Swi				
Twin Earth Termin				
Neon Indica			Indicator Colour	Orange
Minimum Back Box Depth (m				Orange
Ingress Protect	,			
Operational Temperature (
Warranty (Yea	,			
Standards BSE	N 60669-1			
Ensi diag Bare All w prop prop All p	eaning / polishing of products, use only a soft, dry, clean cloth. e that the mains supply is isolated before commencing installation and refer to the circuit am with the relevant product. earth cables must always be covered with appropriate sleeving and wired to the earth terminal. ite moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent rties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral rties against enveloped and non-enveloped viruses. oducts have been independently tested with 99.9% of enveloped viruses and 92% of non- oped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of			

bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

OC ECA

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (14/09/22) Errors & Omissions excluded. Specification is subject to change without notice.