

Ei144RC - Heat Alarm

Mains Powered 230V~ Alkaline Battery Back-up

Key Features

- Remote Test + Control – Wired & Wireless
- Integrated Piezo-electrical sounder
- Easi-fit base
- Test/Silence button
- Memory
- Low battery Indication
- Hardwire Interconnect
- Wireless Interconnect when fitted with Ei168RC
- Kitemarked to BS 5446-2:2003
- 5 year guarantee

Product Description

The Ei144RC is Heat Alarm with 230V AC mains power supply and replaceable Alkaline battery back-up.

The Ei140RC family of Alarms have been designed for households and similar residential applications including HMO's (Houses in multiple occupation)

The Ei144RC is supplied with the Easi-fit base to facilitate quick and simple installation, combined with simple detector head removal and replacement. The Easi-fit base automatically connects both mains power and battery as the detector head slides on.

The Ei144RC may operate as a standalone Alarm or may be interconnected to other Alarms via a wired or wireless system. For a wireless system each Alarm must be fitted with an Ei168RC RadioLINK base. When interconnected all alarms in the system will sound if a fire is detected.

The Alarm is fitted with a Test / Silence button to facilitate frequent testing of your Alarm and System. The Silence function allows the Alarm / System to be silenced in the case of a false / nuisance alarm, e.g. cooking fumes.

The Ei144RC is fitted with a mains "power on" green LED indicator and yellow LED indicator for fault conditions.

The memory feature allows an Alarm that has previously activated to be easily identified.



Technical Specification

Sensor Type:	Thermistor
Supply Voltage:	230V AC, 50Hz
Battery back-up:	9V Alkaline Replaceable
Sound Level:	85 dB(A) at 3 meters
Temperature:	Operating - 0 to 40°C Storage - 0 to 35°C (in a dry area)
Humidity Range:	15% to 95% Relative Humidity
Button Test:	Simulates a high temperature to check the Thermistor, electronics and horn
Insect Screen:	Prevents insects or debris entering chamber (1.00mm mesh size)
Plastic material:	UL94VO flame retardant
Dimensions:	Product - 150mm x 60mm Package - 155mm x 155mm x 70mm
Weight:	350g (incl. Pkg.)
Warranty:	5 year (limited) warranty
Approvals:	



Kitemarked to
BS 5446-2:2003

Specifications are subject to change