# **Product datasheet**

Specifications



## control relay, TeSys K, 4P(2NO+2NC), 690V, 230V AC standard coil

CA2KN22P7

#### Main

Range	TeSys
product name	TeSys CAK
Product or component type	Control relay
Device short name	CA2K
Contactor application	Control circuit
Utilisation category	AC-15 DC-13
Pole contact composition	2 NO + 2 NC
[Ue] rated operational voltage	<= 690 V <= 400 Hz
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz

#### Complementary

[Ith] conventional free air thermal current	al 10 A (at 50 °C)	
Irms rated making capacity	110 A conforming to IEC 60947	
Associated fuse rating	10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660	
[Ui] rated insulation voltage	690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14	
Mounting support	Rail Plate	
Connections - terminals	Screw clamp terminals 1 cable(s) 1.54 mm <sup>2</sup> solid Screw clamp terminals 2 cable(s) 1.54 mm <sup>2</sup> solid Screw clamp terminals 1 cable(s) 0.754 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm <sup>2</sup> flexible without cable end Screw clamp terminals 1 cable(s) 0.341.5 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm <sup>2</sup> flexible without cable end	
Tightening torque	<ul> <li>1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm</li> <li>1.3 N.m - on screw clamp terminals - with screwdriver Philips No 26 mm</li> <li>1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2</li> </ul>	
Control circuit voltage limits	Drop-out: 0.20.75 Uc (at <50 °C) Operational: 0.81.15 Uc (at <50 °C)	
Operating time	1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing 1525 ms coil de-energisation and NC closing 515 ms coil energisation and NC opening	
Mechanical durability	10 Mcycles	

Life Is On Schneider

Maximum operating rate	10000 cyc/h
Immunity to microbreaks	2 ms
Inrush power in VA	30 VA (at 20 °C)
Hold-in power consumption in VA	4.5 VA (at 20 °C)
Heat dissipation	1.3 W
Minimum switching voltage	17 V
Minimum switching current	5 mA
Non overlap distance	0.5 mm
Insulation resistance	> 10 MOhm
Height	58 mm
Width	45 mm
Depth	57 mm
Product weight	0.18 kg

#### Environment

Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product certifications	CB Scheme CCC UL CSA EAC CE UKCA	
IP degree of protection	IP2X	
Protective treatment	TC conforming to IEC 60068	
Ambient air temperature for operation	-2550 °C	
Ambient air temperature for storage	-5080 °C	
Operating altitude	2000 m without derating	
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical robustness	Vibrations contactor open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	6.200 cm
Package 1 Length	4.800 cm
Package 1 Weight	179.000 g
Unit Type of Package 2	S02

Number of Units in Package 2	50
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.280 kg
Unit Type of Package 3	P06
Number of Units in Package 3	400
Package 3 Height	45.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	83.340 kg

## Logistical informations

Country of origin

FR

# **Contractual warranty**

Warranty

18 months

### 🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# Environmental footprint Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 59

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 59
Environmental Disclosure Product

Product Environmental Profile

#### **Use Better**

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

#### Use Again

$^{igcelow}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins