

thermal overload relays, TeSys Deca, 23...32A, class 10A

LRD3353

Main

| Range | TeSys |
|-------------------------------------|--|
| product name | TeSys LRD TeSys Deca |
| Product or component type | Differential thermal overload relay |
| Device short name | LRD |
| Relay application | Motor protection |
| Product compatibility | LC1D80 LC1D95 |
| Network type | AC DC |
| Thermal overload class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 2332 A |
| [Ui] rated insulation voltage | Power circuit: 1000 V conforming to IEC 60947-4-1 Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL |

Complementary

| Network frequency | 0400 Hz | |
|---|--|--|
| Mounting support | Plate, with specific accessories Rail, with specific accessories Under contactor | |
| Tripping threshold | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1 | |
| Auxiliary contact composition | 1 NO + 1 NC | |
| [Ith] conventional free air thermal current | 5 A for signalling circuit | |
| Permissible current | 0.72 A at 500 V AC-15 for signalling circuit 0.06 A at 440 V DC-13 for signalling circuit | |
| [Ue] rated operational voltage | 1000 V AC 0400 Hz for power circuit conforming to IEC 60947-4-1 | |
| Associated fuse rating | 4 A gG for signalling circuit 4 A BS for signalling circuit | |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1 | |
| Phase failure sensitivity | Tripping current 130 % of Ir on two phase, the last one at 0 | |
| Control type | Red push-button: stop Blue push-button: reset | |
| Temperature compensation | -2060 °C | |

| Connections - terminals | Power circuit: screw clamp terminals 1 cable(s) 435 mm² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 435 mm² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 435 mm² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² solid without cable end | |
|-------------------------|--|--|
| Tightening torque | Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 9 N.m - on screw clamp terminals | |
| Height | 81 mm | |
| Width | 70 mm | |
| Depth | 115 mm | |
| Product weight | 0.51 kg | |

Environment

| Climatic withstand | conforming to IACS E10 | |
|---------------------------------------|--|--|
| IP degree of protection | IP20 conforming to IEC 60529 | |
| Ambient air temperature for operation | -2060 °C without derating conforming to IEC 60947-4-1 | |
| Ambient air temperature for storage | -6070 °C | |
| Flame retardance | V1 conforming to UL 94 | |
| Mechanical robustness | Vibrations: 6 Gn conforming to IEC 60068-2-6 Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7 | |
| Dielectric strength | 2.2 kV at 50 Hz conforming to IEC 60947-1 | |
| Standards | EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495 | |
| Product certifications | IEC UL CSA CCC EAC ATEX INERIS UKCA | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.0 cm |
| Package 1 Width | 8.8 cm |
| Package 1 Length | 12.0 cm |
| Package 1 Weight | 498.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |

| Package 2 Weight | 6.32 kg |
|------------------------------|-----------|
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 192 |
| Package 3 Height | 77.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 60.0 cm |
| Package 3 Weight | 109.62 kg |

Logistical informations

Country of origin FR

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 6 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|-------------------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | REACh Declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|-------------------------|
| Circularity Profile | End of Life Information |
| Take-back | No |