

## Motion detector

# IS 140-2

EAN 4007841608811



### Functional description

Are you toying with the idea of fitting a motion detector to your building? The infrared controlled IS 140-2 motion detector gives you all the benefits of a modern detector. Needless to say, we always use the very latest technology for our bestsellers too. For instance, we have given the product in its current generation even more class: larger adjustment angle, even longer reach and even better detection performance. Treat your home to intelligent sensor technology.

### Technical specifications

|  |   |
|--|---|
| <b>Model</b>   | Movement sensor   |
| <b>Sensor type</b>                                   | Passive infrared  |
| <b>Accessories</b>                                   | inkl. Aufputzadapter  |
| <b>Detection angle</b>                               | 140° with sneak-by protection                                 |
| <b>Reach</b>   | 14 m max. (temperature-stabilised)                            |
| <b>Application</b>                                   | indoors and outdoors  |
| <b>Installation</b>                                  | Wall  |
| <b>Dimensions(w x h x d):</b>                        | 70 x 86 x 95 mm   |
| <b>Voltage</b>                                       | 230-240 V/50 Hz   |
| <b>Output</b>  | Max. 1000 W, max. 6 fluorescent lamps / LED lamps, C < 132 µF |
| <b>Capability of masking out individual segments</b> | Yes   |
| <b>Swivelling range</b>                              | 180 °   |
| <b>Tilting range</b>                                 | 90 °  |
| <b>Teach-function for response value luminosity</b>  | No  |
| <b>Time setting</b>                                  | 8 sec. - 35 min.  |
| <b>Degree of protection (IP)</b>                     | IP54  |
| <b>Protection class</b>                              | II  |
| <b>Temperature</b>                                   | -20-50 °C   |
| <b>Housing</b>                                       | UV-resistant plastic  |
| <b>Version</b>                                       | Black   |